


MB-RGBW-251-K-B5


Machine illumination with signal light element

- High light intensity thanks to most modern power LEDs
- Easy operation even without IO-Link possible
- High colour rendering guarantees safety at the workplace according to DIN EN 12464-1 / EN 12464-1
- Large light field for an optimal display of the machine status
- Per IO-Link free parameterizable functions
- Long-life thanks to intelligent thermal management
- Homogeneous wide light field for the optimal machine illumination
- Can be used immediately by 3 color pre-sets: red - green - yellow
- High protection class IP 67
- Magnetic Holder Set available as an option
- Adjustable Mounting Bracket available as an option
- Attachable Diffusion filter available as an option



Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.
 These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)		+20°C, 24V DC
Operating modes		RGB: constant, blink, flash
Illuminated area		30 x 220 mm
Light colour		White (5000 K), RGB + custom
Emission angle FWHM		120°
Luminous flux		440 lm
Illumination intensity		720 Lux (0.5 m / 100%) 220 Lux (1.0 m / 100%)
Service voltage		24 V DC ± 5%, (Supply Class 2)
No-load current		305 mA, (24 V DC)
Trigger input low level		< 5,0 V
Trigger input high level		> 8,0 V
Trigger input		3 color pre-sets: selectable by Trigger 1 + 2, white: selectable by Trigger 3
Interface		V1.1, COM2 (38,4kBd), 2300 µs, for parameterization
Power		7,3 W (24 V DC)
Inverse polarity protection		Yes
Ambient temperature, operation		0 ... +40 °C
Protection class		IP 67
Protection degree		III, operation on protective low voltage
Risk group (DIN EN 62471)		Free group
Casing material		Aluminium nature anodized
Material		PU, crystal clear (Window)
Connection		Cable, 0,3 m, with connector, M12, 5-poled

MB-RGBW-251-K-B5

Machine illumination with signal light element

TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
Light intensity can be adjusted	RGB, 10 ... 100%, by IO-Link
Weight	210 g
Connecting cable	VK ... /5
Cable length max.	25.0 m, (5 x 0.34 mm ² / 24.0 V DC)